

WHEN USING A 17" REAR WHEEL, COMPRESSION OF THE REAR SUSPENSION OR A SHORTER SWAY BAR LINK IS REQUIRED										
17x11 TO BE USED WITH WIDE BODY APPLICATIONS										
6 PISTON/ HELLCAT FRONT BRAKE APPLICATIONS REQUIRE AN 18X5.00 OR 20X6.00 FRONT WHEEL, 20X9 REQUIRES HUBCENTRIC SPACER										
15-CURRENT Chrysler/Dodge AWD 5x115, 71.5mm id, 14mm x 1.5, 35-45mm OE OD 29.2"										
oe front	19	7.50			55.00		6.42	2.08		
oe rear	19	7.50			55.00		6.42	2.08		
	dia.	width	part # prefix	part # suffix	offset mm	adj offset	bospace in	fspace in	stick out/ oe	32
front	17	4.50	92	-745442	-25.40	-6.00	2.51	1.99	0.90	92
front	17	7.00	92	-770447	6.40	25.00	4.98	3.02	0.93	XX
rear	17	9.50	92	-795153	43.50	62.00	7.69	2.81	0.72	XX
rear	20	6.00	92	-060446	-8.90		3.15	3.85	1.77	XX
front/ rear	20	9.00	92	090451	22.00		5.87	4.13	2.05	XX
notes	c/c									
WHEN USING A 17" REAR WHEEL, COMPRESSION OF THE REAR SUSPENSION OR A SHORTER SWAY BAR LINK IS REQUIRED										
17x11 TO BE USED WITH WIDE BODY APPLICATIONS										
6 PISTON/ HELLCAT FRONT BRAKE APPLICATIONS REQUIRE AN 18X5.00 OR 20X6.00 FRONT WHEEL, 20X9 REQUIRES HUBCENTRIC SPACER										
20x6 tire Bridgestone Ecopia 195x50r20										